

The Norton logo is displayed in white, italicized, sans-serif capital letters within a blue, trapezoidal shape that has a slight 3D effect with a white shadow on the right side.

## Concrete & Asphalt ► **PC13P18 Floor Saw**

The Norton Pro-cut PC13P18 is an all new compact floor saw used for wet or dry cutting of asphalt and concrete. Combining economy with high performance, the PC13P18's outstanding cutting results are achieved by its optimal weight distribution. The unique positioning of the 5 gallon water tank adds additional ballast and cutting performance to the blade while maintaining an excellent view of the cutting operation.

The cutting depth is adjustable to a maximum of 6-1/2". The handlebars are adjustable and stay level at any cutting depth for improved operators ergonomics. The newly designed heavy-duty frame reduces vibration to a minimum thereby increasing machine life and operator comfort. For best performance, always use genuine Norton Pro-cut diamond blades.

The Pro-Cut Products logo features a stylized 'P' and 'C' in a blue square, followed by the text 'RO-CUT' in a bold, sans-serif font, and 'PRODUCTS' in a smaller, spaced-out font below it.

NORTON CONSTRUCTION PRODUCTS

**Concrete & Asphalt ▶ PC13P18 Floor Saw**

**FEATURES**

- ▶ Positive continuous screw feed depth control with hand wheel.
- ▶ Four V-belt drive for maximum power.
- ▶ Cutting depth up to 6-1/2" with 18" blade.
- ▶ Removable 5-gallon water tank with large opening for filling. Built-in fitting for external water supply.
- ▶ Handlebars easily adjust to the height of the operator. The handlebars remain at the same level at any cutting depth.
- ▶ Vibration reducing heavy duty frame.
- ▶ Balanced frame design for outstanding cutting performance.
- ▶ Machined flats on tight collars make easy blade removal. Pivoting blade guard for fast, easy blade changes.
- ▶ Standard dual arbor blade shaft for left or right side cutting.
- ▶ Lifting bail at the center of gravity of the saw.
- ▶ All necessary tools stored on saw control panel.
- ▶ Easy access grease fittings on rear wheels and blade shaft bearings.
- ▶ Recessed rear wheels allow for cutting parallel to an open trench.
- ▶ Heavy-duty pillow block bearings on a 1-1/4" dual arbor blade shaft.

**SPECIFICATIONS**

**MODEL:**

Model PC13P18 13HP (9.6 kW)

Honda GX390 gasoline engine with cyclone air filtration and low oil alert

**CHARACTERISTICS:**

Max. Blade	18 inch (400mm)
Blade Diameter	Max Cut Depth
18 inch (400mm)	6.5 inch (140 mm)
14 inch (356mm)	4.5 inch (114mm)
Arbor Size	1.0 in (25.4)
Blade Shaft Speed	2850 rpm
V-Belts	Four
Water Capacity	5 Gallons (20 L)
Sound Pressure	88 dB(A)
Sound Power	105 dB(A)

**DIMENSIONS / WEIGHTS**

Length (Working)	45.5 inch	1160mm
Length (Transport)	33.5 inch	850mm
Width	20.18 inch	512mm
Height	39.0 inch	990mm
Weight	218 lbs	99kg



**ERGONOMICALLY DESIGNED FOR EASY OPERATION**



**EASY BLADE MOUNTING**



**EASY ACCESS WATER TUBES**



**DESIGNED FOR GENUINE NORTON DIAMOND BLADES**

Saint-Gobain Abrasives, Inc.  
2270 West Washington Street  
Stephenville, TX 76401-3798 USA

Tel: (254) 918-2311  
Fax: (254) 918-2312

Sold and supported by: